AMENDMENTS TO THE CLAIMS:

10/577773 IAP17 Rec'd FCT/PTO 28 APR 2006

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS:

Claims 1-10 (Canceled)

- 11. (New) An information recording apparatus comprising:
- a recording device for recording information onto an information recording medium;
- a detrack detecting device for detecting occurrence of detrack during the recording of the information;
- a controlling device for controlling said recording device to return to a location where the detrack has occurred and restart the recording if the occurrence of the detrack is detected;
- a first judging device for judging whether or not the information already recorded in an area of a detrack destination can be reproduced, in the case in which the occurrence of the detrack is detected and the information is already recorded in the area of the detrack destination into which said recording device incorrectly records; and
- a second judging device for judging whether or not error correction can be performed with respect to the area of the detrack destination, in the case in which the occurrence of the detrack is detected and the information is unrecorded in

the area of the detrack destination into which said recording device incorrectly records.

12. (New) The information recording apparatus according to claim 11, wherein

said information recording apparatus further comprises a buffer of a predetermined size for buffering the information and supplying it to said recording device, and

said controlling device controls said buffer and said recording device to restart the recording from a location where the recording is to be restarted with using the information stored in said buffer.

- 13. (New) The information recording apparatus according to claim 12, wherein the predetermined size is equal to or greater than an error-correctable minimum unit.
- 14. (New) The information recording apparatus according to claim 11, wherein

said controlling device controls said recording device to return to the location where the detrack has occurred and restart the recording in such a condition that it is judged that the information can be reproduced or that the error correction can be performed.

- 15. (New) The information recording apparatus according to claim 11, wherein said controlling device controls said recording device to register the area of the detrack destination, as an unallocated area, and to return to the location where the detrack has occurred and to restart the recording if it is judged that the information cannot be reproduced or that the error correction cannot be performed.
- 16. (New) The information recording apparatus according to claim 11, wherein said controlling device controls said recording device to further register the area of the detrack destination incorrectly recorded, as a caution area if it is judged that the information can be reproduced or that the error correction can be performed.
- 17. (New) The information recording apparatus according to claim 11, wherein said controlling device controls said recording device to register the caution area as an unallocated area if the area of the detrack destination is the caution area.
- 18. (New) The information recording apparatus according to claim 11, wherein said controlling device controls said recording device to register an area in another layer corresponding to the area of a detrack destination in one

layer incorrectly recorded, as an unallocated area, when the information recording medium is an information recording medium having a multiple recording layers.

- 19. (New) An information recording method comprising:
- a recording process of recording information onto an information recording medium;
- a detrack detecting process of detecting occurrence of detrack during the recording of the information;
- a controlling process of controlling said recording device to return to a location where the detrack has occurred and restart the recording if the occurrence of the detrack is detected;
- a first judging process of judging whether or not the information already recorded in an area of a detrack destination can be reproduced, in the case in which the occurrence of the detrack is detected and the information is already recorded in the area of the detrack destination into which said recording device incorrectly records; and
- a second judging process of judging whether or not error correction can be performed with respect to the area of the detrack destination, in the case in which the occurrence of the detrack is detected and the information is unrecorded in the area of the detrack destination into which said recording device incorrectly records.

20. (New) A computer program product in a computerreadable medium for record control and for tangibly embodying
a program of instructions executable by a computer provided
for the information recording apparatus, said computer program
product making the computer function as at least one portion
of a recording device, a detrack detecting device, a
controlling device, a first judging device and a second
judging device,

said information recording apparatus comprising:

said recording device for recording information onto an information recording medium;

said detrack detecting device for detecting occurrence of detrack during the recording of the information;

said controlling device for controlling said recording device to return to a location where the detrack has occurred and restart the recording if the occurrence of the detrack is detected;

a first judging device for judging whether or not the information already recorded in an area of a detrack destination can be reproduced, in the case in which the occurrence of the detrack is detected and the information is already recorded in the area of the detrack destination into which said recording device incorrectly records; and

a second judging device for judging whether or not error correction can be performed with respect to the area of the detrack destination, in the case in which the occurrence of the detrack is detected and the information is unrecorded in the area of the detrack destination into which said recording device incorrectly records.